




PLYWOOD

CATALOGUE

KEGO COMPANY LIMITED

Tax ID: 0105492983 | **Phone:** (+84) 24 3222 2333







About us

supplier in Vietnam. With the slogan "Local to Global", we have proudly exported to more than 50 countries and are continuously expanding to provide Vietnamese plywood worldwide.



Content



Commercial Plywood	P3
Packing Plywood	
Film Faced Plywood	
Container Flooring Plywood	P6
Laminated Veneer Lumber	P7













COMMERCIAL **PLYWOOD**



Material

Face/Back: Bintangor, Okoume, Sapele, Pine, Engineering, etc.

4.6/8/9/11/12/14/15/17/18/24 (customized)

Core: Eucalyptus, Acacia, Mixed Hardwood

Glue: UF (E0/E1/E2), MUF

Size: 1220x2440, 1220x1840, 910x1820, 915x1830, 920x1840 (customized)

Dimension

(mm) Thickness tolerance: $\pm 0.3 - 0.5$

> Moisture content: ≤ 14%

Thickness:

Technical Performance

Application

550 - 700 kg /CBM Wood density:

Sanding 2 sides, 2 times hot press, 1 time cold press Sanding/Press:

Polishing: 2 faces (optional)

Furniture:

Wardrobes, tables, cabinets, shelves, etc.

Construction:

Flooring, roofing, walls, partitions, etc.

Interior design:

Paneling, ceiling tiles, wall coverings, etc.









PACKING PLYWOOD

Face/Back: • Grade AA: Bintangor/ Bintangor

• Grade AB: Bintangor/ Styrax

• Grade BC: Styrax/ Styrax **Material** Core: Acacia, Mixed Hardwood

> Glue: UF (E1/E2)

> Size: 1220x2440

Dimension Thickness: 2.0/2.5/4.6/8/9/11/12/14/15/17/18/22 (customized) (mm)

Thickness tolerance: ± 0.5

Moisture content: ≤ 14%

Technical Wood density: 500 - 550 kg/CBM **Performance**

Sanding/Press: No sanding, 1 time hot press

Packaging materials: Wooden pallets, crates, boxes, shelves, etc.

Application Furniture: Bed frames, sofa frames, etc.









FILM FACED **PLYWOOD**

Material	Face/Back:	Plain Film (Black/Brown/Red), Logo Film
	Core:	Eucalyptus, Acacia, Rubber, Mixed Hardwood
	Glue:	MUF, PF
	C:	1220-2440-1250-2500-010-1020-610-2440-610-2500
Dimension (mm)	Size:	1220x2440, 1250x2500, 910x1820, 610x2440, 610x2500
	Thickness:	11/11.5/12/15/18/21 (customized)
	Thickness tolerance:	± 0.5
	Moisture content:	≤ 12%
Technical Performance	Reuse:	4 - 6 times, 6 - 8 times, 8 - 12 times, 15 - 20 times
	Wood density:	600 - 700 kg/CBM
	Sanding/Press:	Sanding 2 sides, 2 times hot press, 1 time cold press
	Construction:	Formwork, scaffolding, flooring, etc.
Application	Marine uses:	Boat flooring, docks, etc.
	Furniture:	Shelves, cabinets, countertops, partitions, etc.









CONTAINER **FLOORING PLYWOOD**



Material Core: Eucalyptus, Keruing Glue: MUF, PF Size: 1160x2400, 635x2400, 550x2400 (customized) **Dimension** Thickness: (mm) Thickness tolerance: ± 1 Certificates: IICL (T5, T6, T7), Dekra Test, Flexible Test, Boiling Test **Technical** Weight: 58 - 75 kg/sheet **Performance** Plies: 21 - 23 ≤ 12% *Moisture content:* Container flooring, truck flooring, railcar flooring, etc.

Keruing/ Engineering veneer/ Film



Flooring:

Construction:

Face/Back:



Modular buildings, portable site offices, etc.



Application



LAMINATED **VENEER** LUMBER (LVL)



Material

Face/Back: Styrax, Acacia, Pine, Mixed Wood

> Core: Acacia, Mixed wood

Glue: UF (E0/E1/E2)

Length: ≤ 5000

Dimension (mm)

Width: 20 - 200 Thickness: 9 - 95

Thickness tolerance: ± 1

Technical Performance Certificates: JAS, FSC, etc.

Moisture content: ≤ 12%

Sanding/Press: No sanding, 1 time hot press, 1 time cold press

Construction: Beams, headers, lintels, I - joists, etc.

Application

Packaging materials: Pallets, boxes, shelves, etc.

Sofa frame, flush doors, bed frames, etc. *Furniture frame:*

















KEGO COMPANY LIMITED

Tax ID: 0105492983

Address: R.603 Kim Anh Building, Lane 78, Duy Tan Street,

Cau Giay District, Hanoi City, Vietnam

Email: sales@kego.com.vn | **Phone:** (+84)24 3222 2333







whatsapp 🔺